

EX3260 SVGA 3LCD Projector

Contact Us 800.463.7766

Mon-Fri 7am-4pm PT



Reliable, portable projector with fast, easy setup and performance.

Present with ease and confidence with the EX3260 portable projector. Featuring 3,300 lumens of color/white brightness¹, this reliable performer delivers vibrant images — even in well-lit spaces. Offering SVGA resolution (800 x 600), the EX3260 is ideal for everyday projection needs. A host of innovative setup features, including easy image adjustments, help you get up and running in no time. It also supports HDMI®, for compatibility with laptops and media players. Plus, Epson® 3LCD projectors deliver remarkable color accuracy, with high Color Brightness² and wide Color Gamut³.

Projection System: 3LCD, 3-chip technology

Native Resolution: 800 x 600 (SVGA)

Color Brightness: 3300 lumens¹

White Brightness: 3300 lumens¹

Throw Distance Calculator


Model: V11H842020

OUR PRICE:

~~\$400.00~~

AFTER 20% SAVINGS:

\$399.99

 Save \$100 Today

★★★★★ (59) [Write a review](#)

Overview

Bright and Colorful

Features 3300 lumens of color brightness (color light output)¹ and 3300 lumens of white brightness (white light output)¹.

SVGA Resolution

800 x 600 resolution

Manual Keystone Correction

Adjusts vertically and horizontally to easily achieve a perfect rectangular image.

HDMI Connectivity

Includes all-digital, HDMI audio and video connection, for HD quality with just one cable

- **More accurate, vivid color, even in well-lit rooms** — 3,300 lumens of equal color and white brightness¹
- **SVGA resolution (800 x 600)** — ideal for projecting everyday presentations and graphics
- **Fast, easy setup with Epson** — get up and running in no time with easy image adjustments and convenient control
- **Remarkable color accuracy** — High Color Brightness² and wide Color Gamut³ with Epson
- **Works with the latest laptops and media players** — supports HDMI, the standard in connectivity, for digital video and audio in one cable
- **Portability you need for presentations on the go** — carrying case included
- **USB Plug 'n Play** — use the included USB cable to instantly project content from a PC or Mac®

Eco Features

- RoHS compliant
- Recyclable product⁴
- Epson America, Inc. is a SmartWay™ Transport Partner⁵

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ►

What's In The Box:

- EX3260 projector
- Power cable
- Computer cable (VGA)
- USB cable

- Soft carrying case
- Projector remote control
- Batteries
- User manual CD
- Quick Setup Sheet

Specifications

Specifications Projector:

Projection System:

Epson 3LCD, 3-chip technology

Projection Method:

Front / rear / ceiling mount

Driving Method:

Epson Poly-silicon TFT Active Matrix

Pixel Number:

480,000 dots (800 x 600) x 3

Color Brightness - Color Light Output:

3300 lumens¹

White Brightness - White Light Output:

3300 lumens¹

Aspect Ratio:

4:3

Resolution:

800 x 600 (SVGA)

Resize:

1024 x 768 (XGA), 1152 x 864 (SXGA), 1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1440 x 900 (WXGA+), 1400 x 1050 (SXGA+)

Lamp Type:

210 W UHE

Lamp Life:

- ECO mode: Up to 10000 hours⁶
- Normal mode: Up to 6000 hours⁶

Throw Ratio Range:

1.48 (Zoom:Wide), 1.77 (Zoom:Tele)

Size - projected distance:

30" – 350" (0.88 – 10.44 m)

Keystone Correction:

- Automatic: Vertical: ±30 degrees
- Manual: Horizontal: ±30 degrees (Easy-Slide Horizontal Image Correction)

USB Plug 'n Play:

- Projects audio and video
- PC and Mac® compatible

Contrast Ratio:

Up to 15,000:1

Color Reproduction:

Up to 1.07 billion colors

General:

Temperature:

41° to 95° F (5° to 35° C)

Weight:

5.51 lb

Security:

- Kensington®-style lock provision
- Password protect function

Projection Lens:

Type:

Digital zoom (Manual)/Focus (Manual)

F-number:

1.44

Focal Length:

16.7 mm

Zoom Ratio:

Digital zoom 1.0 – 1.35

Projector Details:

Display Performance:

- NTSC: 480 lines
- PAL: 576 lines
(Depends on observation of the multi-burst pattern)

Input Signal:

NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM

Interfaces:

- HDMI x 1
- Computer / Component video: D-sub 15 pin x 1
- S-video: Mini DIN x 1
- Composite video: RCA (Yellow) x 1
- Audio in: RCA x 1 (White / Red)
- USB connector Type A x 1: PC-free USB and other
- Wireless LAN
- USB connector Type B x 1: USB Plug 'n Play

Speaker:

2 W (mono)

Fan Noise:

- ECO mode: 28 dB
- Normal mode: 37 dB

Projector Dimensions:

Including feet:

11.9" x 9.9" x 3.6" (W x D x H)

Excluding feet:

11.9" x 9.8" x 3.4" (W x D x H)

Remote Control:

Features:

Source search selection, power, volume, e-zoom, A/V Mute, freeze, menu, page up and down, help, auto, mouse functions

Operating Distance:

19.7 ft (6 m)

Operating Angle:

- Right / Left: ± 30 degrees
- Upper / Lower: ± 15 degrees

Power:

Power Supply Voltage:

100 – 240 V $\pm 10\%$, 50/60 Hz

Power Consumption:

- ECO mode: 211 W
 - Normal mode: 296 W
-

© 2021 Epson America, Inc.