

OUT OF STOCK

PowerLite 118 3LCD XGA Classroom Projector with Dual HDMI

Contact Us 800.463.7766

Mon-Fri 7am-4pm PT



Enhance your classroom with ultra bright, 3,800-lumen projection¹

Enrich lesson plans with the ultra bright PowerLite 118 projector. Built with advanced 3LCD technology, this dynamic XGA projector displays vibrant images with 3,800 lumens of color and white brightness¹. Featuring an integrated Moderator function², the PowerLite 118 allows up to 50 users to connect to the display and share content from laptops or mobile devices³. A durable and reliable solution, it features a long lamp life up to 17,000 hours⁴, a 16 W speaker, a microphone input, and dual HDMI ports to support versatile and engaging projection in a variety of learning environments.

- 3,800 lumens of color and white brightness¹
- Native XGA resolution and 4:3 performance
- Long lamp life up to 17,000 hours in ECO Mode⁴
- Built-in Moderator function² for easy sharing
- Advanced network connectivity
- **THROW DISTANCE AND DISPLAY SIZE CALCULATORS ►**

Model: V11HA03020

OUR PRICE :

\$519.00[Write a review](#)

Overview

3-chip 3LCD technology for Best-in-Class Color Brightness⁵

3,800 lumens of color and white brightness¹

Native XGA resolution and a 4:3 aspect ratio

for vibrant, colorful images

Low-priced, long-lasting lamp

up to 17,000 hours in ECO Mode⁴

Moderator function²

allows up to 50 users to connect to the display simultaneously; perfect for displaying a variety of content or comparing students' work side-by-side

Advanced network connectivity

RJ-45 allows remote network projector management, presentations over the network, and more

Project from laptops and mobile devices

wirelessly display from PC, Mac®, Chromebook™, iOS® and Android™ devices³

- **Easy setup and positioning flexibility** — offers 1.2x optical zoom, ±30 degrees horizontal and vertical keystone correction, and Quick Corner®
- **Dual HDMI ports** — supports multiple high-definition AV devices
- **Built-in 16 W speaker and microphone input** — for engaging projector displays
- **Screen size up to 300"** — with Split Screen⁶ capability for side-by-side viewing

Eco Features

- RoHS compliant
- Recyclable product⁷
- Epson America, Inc. is a SmartWay™ Transport Partner⁸

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ►

What's In The Box:

- PowerLite 118 Projector
- Power cord
- Computer cable (VGA)

- Projector remote control
- Batteries
- User Manual CD
- Software CD
- Quick setup sheet
- Warranty card
- Password protect sticker

Specifications

Specifications Projector:

Projection System:

3LCD, 3-chip technology

Projection Method:

Front / rear / ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

786,432 dots (1024 x 768) x 3

Color Brightness - Color Light Output:

3800 lumens¹

White Brightness - White Light Output:

3800 lumens¹

Aspect Ratio:

4:3

Resolution:

1024 x 768 (XGA)

Resize:

640 x 480 (VGA), 800 x 600 (SVGA), 1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1366 x 768 (WXGA60-3), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1680 x 900 (WXGA++), 1600 x 1200 (UXGA60)

Lamp Type:

210 W UHE

Lamp Life:

- ECO mode: Up to 17,000 hours⁴
- Medium mode: Up to 10,000 hours⁴
- Normal mode: Up to 8,000 hours⁴

Throw Ratio Range:

1.48 (Zoom:Wide), 1.77 (Zoom:Tele)

Size - projected distance:

30" to 300" (0.89 to 9.12 m) (Zoom:Wide)

Keystone Correction:

- Vertical: ±30 degrees (Automatic)

- Horizontal: ± 30 degrees (Slider)

USB Plug 'n Play:

Projector is compatible with PC and Mac® computers

Contrast Ratio:

Up to 16,000:1

Color Processing:

10 bit

Color Reproduction:

Up to 1.07 billion colors

General:

Temperature:

41° to 95° F (5° to 35° C)

Weight:

6.17 lb (2.8 kg)

Security:

- Kensington®-style lock provision
- Padlock
- Security anchor bar

Power:

Power Supply Voltage:

100 – 240VAC $\pm 10\%$, 50 / 60Hz AC

Power Consumption:

- ECO mode: 235 W
- Normal mode: 345 W
- Communication on: 2.0 W Standby
- Communication off: 0.3 W Standby

Projection Lens:

Type:

Manual focus

F-number:

1.49 – 1.72

Focal Length:

16.9 mm – 20.28 mm

Zoom Ratio:

1.0 – 1.2

Remote Control:

Features:

A/V Mute, Freeze, Split, Aspect, Color Mode, Auto, MHL Menu, Volume

Operating Distance:

19.7' (6 m)

Operating Angle:

- Right / Left: ± 30 degrees
- Upper / Lower: ± 15 degrees

Projector Dimensions:

Including feet:

11.8" x 9.8 x 3.4" (W x D x H)

Excluding feet:

11.6" x 10.2" x 3.6" (W x D x H)

Projector Details:

Display Performance:

- NTSC: 480 lines
 - PAL: 576 lines
- (Depends on observation of the multi-burst pattern)

Input Signal:

NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM

Interfaces:

- 1x USB-A
- 1x USB-B
- 1x LAN
- 2x HDMI
- 2x Computer/Component
- 1x Video
- 1x RS-232c
- 1x Stereo Mini-jack (Mic)
- 1x Monitor Out
- Audio 1 & 2
- Audio L & R
- 1x Audio Out
- Wireless LAN port: 802.11 b/g/n (optional – module sold separately)

Speaker:

16 W (mono)

Fan Noise:

- ECO mode: 28 dB
- Normal mode: 37 dB

Eco Features:

- RoHS compliant
- Recyclable product⁷
- Epson America, Inc. is a SmartWaySM Transport Partner⁸

© 2021 Epson America, Inc.