

OUT OF STOCK

PowerLite 119W 3LCD WXGA Classroom Projector with Dual HDMI

Contact Us 800.463.7766

Mon-Fri 7am-4pm PT



Promote in-class collaboration and engagement with ultra bright, 3LCD projection.

Increase collaboration in the classroom with the PowerLite 119W projector. Designed to maximize engagement and enrich lesson plans, this powerful WXGA projector delivers eye-catching, widescreen displays with 4,000 lumens of color and white brightness¹. Featuring an integrated Moderator function², the PowerLite 119W allows up to 50 users to connect to the display and share content from laptops or mobile devices³. Plus, this durable projector features up to 17,000 hours of lamp life in ECO Mode⁴, a 16 W speaker, a microphone input, and dual HDMI ports to create dynamic, high-definition displays in a variety of learning environments.

- 4,000 lumens of color and white brightness¹
- Native WXGA resolution and 16:10 aspect ratio
- Long lamp life up to 17,000 hours in ECO Mode⁴
- Built-in Moderator function² for easy sharing
- Advanced network connectivity
- **THROW DISTANCE AND DISPLAY SIZE CALCULATORS ►**

Model: V11H985020

OUR PRICE :

\$649.00[Write a review](#)

Overview

3-chip 3LCD technology for Best-in-Class Color Brightness⁵
4,000 lumens of color and white brightness¹

Bright, widescreen images
with native WXGA resolution and a 16:10 aspect ratio

Low-priced, long-lasting lamp
up to 17,000 hours in ECO Mode⁴

Moderator function²
allows up to 50 users to connect to the display simultaneously; perfect for displaying a variety of content or comparing students' work side-by-side

Advanced network connectivity
RJ-45 allows remote network projector management, presentations over the network, and more

Project from laptops and mobile devices
wirelessly display from PC, Mac®, Chromebook™, iOS® and Android™ devices³

- **Easy setup and positioning flexibility** — offers 1.2x optical zoom, ±30 degrees horizontal and vertical keystone correction, and Quick Corner®
- **Dual HDMI ports** — supports multiple high-definition AV devices
- **Built-in 5 W speaker** — for engaging projector displays
- **Screen size up to 320"** — with Split Screen⁶ capability for side-by-side viewing

Eco Features

- RoHS compliant
- Recyclable product⁷
- Epson America, Inc. is a SmartWay™ Transport Partner⁸

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ►

What's In The Box:

- PowerLite 119W Projector

- Power cord
- Computer cable (VGA)
- Projector remote control
- Batteries
- Software CD
- Quick setup sheet
- Warranty card

Specifications

Specifications Projector:

Projection System:

3LCD, 3-chip technology

Projection Method:

Front / rear / ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

1,024,000 dots (1280 x 800) x 3

Color Brightness - Color Light Output:

4000 lumens¹

White Brightness - White Light Output:

4000 lumens¹

Aspect Ratio:

16:10

Resolution:

1280 x 800 (WXGA)

Resize:

640 x 480 (VGA), 800 x 600 (SVGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1366 x 768 (WXGA60-3), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1680 x 900 (WXGA++), 1600 x 1200 (UXGA60)

Lamp Type:

210 W UHE

Lamp Life:

- ECO mode: Up to 17,000 hours⁴
- Medium mode: Up to 10,000 hours⁴
- Normal mode: Up to 8,000 hours⁴

Throw Ratio Range:

1.30 (Zoom:Wide), 1.56 (Zoom:Tele)

Size - projected distance:

33" to 320" (0.91 to 9.07 m) (Zoom:Wide)

Keystone Correction:

- Vertical: ±30 degrees (Automatic)

- Horizontal: ± 30 degrees (Slider)

USB Plug 'n Play:

Projector is compatible with PC and Mac® computers

Contrast Ratio:

Up to 16,000:1

Color Processing:

10 bit

Color Reproduction:

Up to 1.07 billion colors

General:

Temperature:

41° to 95° F (5° to 35° C)

Weight:

6.17 lb (2.8 kg)

Security:

- Kensington®-style lock provision
- Padlock
- Security anchor bar

Power:

Power Supply Voltage:

100 – 240VAC $\pm 10\%$, 50 / 60Hz AC

Power Consumption:

- ECO mode: 235 W
- Normal mode: 345 W
- Communication on: 2.0 W Standby
- Communication off: 0.3 W Standby

Projection Lens:

Type:

Manual focus

F-number:

1.49 – 1.72

Focal Length:

16.9 mm – 20.28 mm

Zoom Ratio:

1.0 – 1.2

Remote Control:

Features:

A/V Mute, Freeze, Split, Aspect, Color Mode, Auto, MHL Menu, Volume

Operating Distance:

19.7' (6 m)

Operating Angle:

- Right / Left: ± 30 degrees
- Upper / Lower: ± 15 degrees

Projector Dimensions:

Including feet:

11.8" x 9.8 x 3.6" (W x D x H)

Excluding feet:

11.6" x 10.2" x 3.4" (W x D x H)

Projector Details:

Display Performance:

- NTSC: 480 lines
 - PAL: 576 lines
- (Depends on observation of the multi-burst pattern)

Input Signal:

NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM

Interfaces:

- 1x USB-A
- 1x USB-B
- 1x LAN
- 2x HDMI
- 2x Computer/Component
- 1x Video
- 1x RS-232c
- 1x Stereo Mini-jack (Mic)
- 1x Monitor Out
- Audio 1 & 2
- Audio L & R
- 1x Audio Out
- Wireless LAN port: 802.11 b/g/n (optional – module sold separately)

Speaker:

16 W (mono)

Fan Noise:

- ECO mode: 28 dB
- Normal mode: 37 dB

Eco Features:

- RoHS compliant
- Recyclable product⁷
- Epson America, Inc. is a SmartWaySM Transport Partner⁸

© 2021 Epson America, Inc.