

OUT OF STOCK

PowerLite E20 3LCD Classroom Projector

Contact Us 800.463.7766

Mon-Fri 7am-4pm PT



Create engaging learning environments with this ultra bright, 3LCD projector.

Get astounding classroom projection at an affordable price point with the PowerLite E20 projector. Featuring advanced 3LCD technology, this ultra bright, 3,400-lumen¹ projector delivers vibrant, true-to-life images with Best-in-Class Color Brightness² and native XGA resolution. Designed specifically for classroom environments, the PowerLite E20 increases engagement and enriches lesson plans with HDMI[®] connectivity and a built-in 5 W speaker. Built to last, this durable projector provides a long lamp life of 12,000 hours in ECO Mode³, plus convenient installation and positioning flexibility for easy projection from anywhere in the classroom.

- 3LCD technology for Best-in-Class Color Brightness²
- Native XGA resolution and 4:3 performance
- Long lamp life up to 12,000 hours in ECO Mode³
- Easy setup and positioning flexibility
- HDMI connectivity
- **THROW DISTANCE AND DISPLAY SIZE CALCULATORS ►**

Model: V11H981020

OUR PRICE :

\$379.00

[Write a review](#)

Overview

3-chip 3LCD technology for Best-in-Class Color Brightness²
3,400 lumens of color and white brightness¹

Native XGA resolution and 4:3 performance
for vibrant, colorful images

Low-priced, long-lasting lamp
up to 12,000 hours in ECO Mode³

Easy setup and positioning flexibility
1.0-1.35x digital zoom, ±30 degrees horizontal and vertical keystone correction and horizontal keystone slider

HDMI Connectivity
get HD quality video and audio with a single cable

Built-in 5 W speaker
for engaging projector displays

- **Screen size up to 350"** — with Split Screen⁴ capability for side-by-side viewing

Eco Features

- RoHS compliant
- Recyclable product⁵
- Epson America, Inc. is a SmartWay™ Transport Partner⁶

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ►

What's In The Box:

- PowerLite E20 Projector
- Power cord
- Computer cable (VGA)
- Projector remote control
- Batteries
- Software CD
- Quick setup sheet
- Warranty card

Specifications

Specifications Projector:

Projection System:

3LCD, 3-chip technology

Projection Method:

Front / rear / ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

786,432 dots (1024 x 768) x 3

Color Brightness - Color Light Output:

3400 lumens²

White Brightness - White Light Output:

3400 lumens²

Aspect Ratio:

4:3

Resolution:

1024 x 768 (XGA)

Resize:

1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3) 1366 x 768 (WXGA60-3), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+)

Lamp Type:

210 W UHE

Lamp Life:

- ECO mode: Up to 12,000 hours³
- Normal mode: Up to 6,000 hours³

Throw Ratio Range:

1.44 (Zoom: Wide), 1.95 (Zoom: Tele)

Size - projected distance:

30" to 350" (0.76 to 10.34 m)

Keystone Correction:

- Automatic: Vertical: ±30 degrees
- Slider: Horizontal: ±30 degrees

USB Plug 'n Play:

Projector is compatible with PC and Mac computers

Contrast Ratio:

Up to 15,000:1

Color Reproduction:

Up to 1.07 billion colors

General:

Temperature:

41 ° to 95 °F (5 ° to 35 °C)

Weight:

5.95 lb (2.7 kg)

Security:

- Kensington®-style lock provision
- Padlock
- Security anchor bar

Power:

Power Supply Voltage:

100 – 240VAC ±10%, 50 / 60Hz AC

Power Consumption:

- ECO mode: 235 W
- Normal mode: 345 W
- Standby: Max 2.0W

Projection Lens:

Type:

Manual focus

F-number:

1.44

Focal Length:

16.7 mm

Zoom Ratio:

Digital zoom 1.0 – 1.35

Remote Control:

Features:

A/V Mute, Freeze, Split, Aspect, Color Mode, Auto, MHL Menu, Volume

Operating Distance:

19.7' (6 m)

Operating Angle:

- Right / Left: ±30 degrees
- Upper / Lower: ±15 degrees

Projector Dimensions:

Including feet:

11.8" x 9.8" x 3.6" (W x D x H)

Excluding feet:

11.8" x 9.8" x 3.4" (W x D x H)

Projector Details:

Display Performance:

- NTSC: 480 lines
 - PAL: 576 lines
- (Depends on observation of the multi-burst pattern)

Input Signal:

NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM

Interfaces:

- 1x USB-B
- 1x HDMI
- 2x Computer/Component
- 1x Video
- 1x RS-232c
- 1x Monitor Out
- Audio 1 & 2
- Audio R & L
- 1x Audio Out

Speaker:

5 W (mono)

Fan Noise:

- ECO mode: 28 dB
- Normal mode: 37 dB

© 2021 Epson America, Inc.